



Paving Asphalt 60/70 S

PENETRATION GRADED ASPHALT PRODUCT

Product Description

Paving Asphalt 60/70 S is a penetration graded asphalt product derived from specially selected crude oils via carefully controlled refining processes.

The quality of ExxonMobil products is assured for every delivery. They are produced and controlled according to the ExxonMobil Product Quality Management System, EN ISO 9000 or equivalent standard.

Applications

Paving Asphalt 60/70 S is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

Properties & Specifications

Paving Asphalt 60/70 S meets the following specification requirements:

Asphalt	Unit	Method	60/70 S
Penetration at 25° C	x 0.1 mm	ASTM D 5	60-70
Softening Point	°C	ASTM D 36	47-56
Ductility at 25° C, 5 cm/min (min)	cm	ASTM D 113	150
Wax content (max)	mass %	DIN EN 12606-1	2
Specific gravity	-	ASTM D 70	1.01-1.05
Flash Point (min)	°C	ASTM D 92	232
Solubility in trichloroethylene (min)	mass %	ASTM D 2042	99.5

Thin Film Oven Test at 163° C (ASTM D1754)

Change of mass (max) +/-	mass %	ASTM D 1754	0.2
Retained penetration (min)	%	ASTM D 5	60
Ductility at 25° C , 5 cm/min (min)	cm	ASTM D 113	100

Above specifications may be subject to change.